



PRODUCTION ENHANCEMENT SYSTEMS, LLC

P.O. BOX 52872

LAFAYETTE, LA 70505

337.849.6340

www.beadlejuice.com

ej@beadlejuice.com

SUPER FOAM B STICKS

SUPER FOAM B STICKS are special foam sticks that contain 100% active surfactants., friction reducer and foam stabilizer in water-soluble tubes. Natural gas bubbling through the water column and 100% active ingredients produces foam which can help remove water from watered-up gas wells.

PRODUCT USES:

SUPER FOAM B STICKS are primarily used to remove water from gas wells and increase gas production. This foaming action decreases the hydrostatic back-pressure which increases gas production that further enhances the foaming action until the well unloads.

SUPER FOAM B STICKS can be used to remove condensate and water from gas condensate wells and flowing oil wells. For wells with more than 75% condensate, it is recommended to use OIL FOAM STICKS.

PRODUCT ADVANTAGES:

SUPER FOAM B STICKS contain 100% active foamer in a water-soluble tube that can produce up to four (4) times more than most other sticks on the market. The entire stick (tube, caps and contents) are water-soluble. The sticks are shipped ready-to-use and will not dissolve while in cool, dry storage.

SUPER FOAM B STICKS can develop stable foam in high temperature deep gas wells. Lab tests indicate that stable foam can be developed at 212°F and above. For extremely high temperature wells the formulation can be altered.

SUPER FOAM B STICKS are an economical way to remove water from gas wells without using expensive well service operations such as swabbing, jetting with coiled tubing or installing artificial lift and siphon strings.

TREATMENT DETERMINATION & PROCEDURE FOR WATER REMOVAL:

The number of SUPER FOAM B STICKS used is based on the volume of water above the perforations. Field tests indicate that the best results were achieved by using a larger initial slug treatment of 1/8 to 1/4 percent by weight would require .44 to .88 lbs. of stick per BBL of water.

DISCLAIMER OF LIABILITY:

The information in this bulletin is believed to be accurate, however all recommendations are made without warranty since the conditions of use are beyond Production Enhancement Systems, LLC., control. Production Enhancement Systems, LLC., disclaims any liability in connection with the use of the information, and does not warrant against infringement by reason of the use of any of its' products in combination with any other material or in any process.